



AquaScat S

How to order?

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8



All articles
include 10m cable
(M12 with 8 pins)

(except column 5)

IO: 0/4..20 mA
Modbus TCP

Profibus DP

Profinet IO

Modbus RTU

Photometer product variants and sets							
AquaScat S + extractable assembly with flange DN65 PN16 + checking unit + SICON	AquaScat S + extractable assembly + checking unit + SICON	AquaScat S + checking unit + SICON M	AquaScat S + checking unit + SICON	AquaScat S Submerge vers. IP68	AquaScat S + adaption of checking unit to another AquaScat S	AquaScat S + checking unit	AquaScat S
							
123104	123100	123097	123096	123552 123553* 123554**	123093	123092	120498
123105	123101	123110	123114				
123106	123102	123111	123108				
123107	123103	123112	123109				

* with 20m cable ** with 30m cable

Accessories

- +

119045

24VDC power supply 20W, input 100–240 VAC/47–63Hz
- +

120497

Checking AquaScat S
- +

120540

Instrument cable 8-pole 20m with connector
- +

120541

Instrument cable 8-pole 30m with connector
- +

120510

Conn-R Box
- 120290

SICON C

Installation

- +

123928

PVC Measuring cell for AquaScat S with connection Ø10
- +

120562

Pipe flange DN40
- +

123781

Pipe flange DN50 PN16
- +

124003

PVC-U Fitting d=63 AquaScat S
- +

124006

Pipe flange DN50 PN16