



ColorPlus3 SAK 254

How to order?

1

2


3


4

5

6

ColorPlus 3 in specified configuration with control unit (Sicon) and 10 m signal cable.



Photometer Produktvarianten und Sets						
	SAK254 + Wandmontage-Set mit Filter	SAK254	SAK254 + Hazen *	Hazen *	SAK254 + SAK436	SAK436
						
IO: 0/4..20 mA Modbus TCP	121140 121141	122827 122831	122837 122838	123990 123991	123992 123993	122839 122843
Profibus DP	122847 122850	122828 122832	-	-	-	122840 122844
Profinet IO	122848 122851	122829 122833	-	-	-	122841 122845
Modbus RTU	122849 122852	122830 122834	-	-	-	122842 122846

Path length 100 mm
Path length 50 mm

* Possible wavelengths for Hazen: 366, 380, 390, 400, 410, 420, 430, 436, 455 nm
** Possible wavelengths: 436, 440, 450, 455, 460, 470, 475, 480, 490, 500, 510, 520, 530, 540, 546, 550, 560, 570, 580, 590, 600, 610, 620, 630, 640, 650, 660, 670, 680, 690, 700, 710, 740, 760 nm
*** Possible wavelengths: 214, 254, 280, 313, 340 nm

Further configurations are available on request: tech.sales@sigrisT.com

Accessories

- + 122062 Hazen calibration certificate
- + 121139 Optical filter for turbidity compensation **
- + 122349 Optical filter UV ***
- + 121060 Wall mounting set for ColorPlus 3 with filtering unit and sample line
- + 121169 Wall mounting set for ColorPlus 3 with accessories sample line (without filtering unit)
- + 120538 Instrument cable 4-pole 20m with connector
- + 120539 Instrument cable 4-pole 30m with connector
- + 124045 24VDC power supply 20W, input 100-240 VAC/47-63Hz