

LabScat 2

How to order?



Communication

IO: 0/4 ... 20 mA

Modbus RTU

Profibus DP

Profinet IO

- ①
- ②
- ③
- ④
- ⑤
- ⑥
- ⑦

Photometer Product variants and sets						
LabScat 2 with or without 50 mm cuvette			LabScat 2	Sets with 50 mm and 25 mm cuvette		
1x cuvette KPL50/190 for temperature control	1x Cuvette KLP50/190	1x Cuvette KLP50/190		1x Cuvette KLP50/190 1x Cuvette KLP25/190	1x Cuvette KLP50/190 1x Cuvette KLP25/190	1x Cuvette KLP50/190 1x Cuvette KLP25/190
Cooling set +	Cooling set			Cooling set + Calibration up to 500 EBC-25mm cuvette, including certificate	Cooling set Calibration up to 500 EBC-25mm cuvette, including certificate	Calibration up to 500 EBC-25mm cuvette, including certificate
122774	122770	122766	119185	123120	122782	122778
122775	122771	122767	122763	123121	122783	122779
122776	122772	122768	122764	123122	122784	122780
122777	122773	122769	122765	123123	122785	122781

Cooling set: Fan for cooling operation

Cooling set+: Fan for cooling operation, temperature control